

# AR-DVR5200/5400E-D Series 1080P HD-DVR

AR-DVR5216E-D / AR-DVR5416E-D

## Key Features



- Auto adjust the frame resource to fit video connected
- All channel synchronous playback
- Plug-in Free, to support IE, Chrome, Firefox, Safari Browser
- All channel synchronous live view and playback by smart phone
- H.264 video Compression
- Up to 16 1080P AHD / Analog camera can be accessed
- HDMI / VGA at up to 1080P
- Supported 2/4HDD and up to 8TB each
- 1 self-adaptive 10/100Mbps RJ45 interface
- Auto record when camera connected

Model		AR-DVR5216E-D	AR-DVR5416E-D
Video / Audio input	AHD video input	16 Ch.	
	Supported camera	BNC interface (1.0Vp-p, 75Ω) types AHD / Analog, 1080P30, 1080P25, 720P30, 720P25, 960H	
	Audio input	4 Ch RCA interface (2.0Vp-p, 1KΩ)	
Video / Audio output	HDMI / VGA output	1080p (1920×1080)/60Hz, 720p (1280×720)/60Hz, UXGA (1600×1200)/60Hz, 1280×1024/60Hz	
	Audio output	RCA (Linear, 1KΩ)	
Video / Audio codec	Video compression	H.264	
	Dual-stream	Support	
	Encoding resolution	1080P (1920×1080), 720P (1280×720), 960H, D1	
	Frame rate	240fps	
	Audio compression	G.711u	
	Synchronous playback	All channel synchronous playback	
HDD	SATA	2× SATA interfaces for 2 HDDs	4× SATA interfaces for 4 HDDs
	Capacity	Up to 8TB capacity for each HDD	
External interfaces	Network	1× 10/100/1000Mbps RJ45 interface	
	USB	Front panel: 1× USB2.0, Rear panel: 1× USB2.0	
	Alarm	4 in / 1 out	
	RS-485	1x RS485 interface	
General	Power supply	12V 40W	12V 90W
	Operating condition	-10°C – 55°C (14°F – 131°F), Humidity 10 - 90%	
	Dimensions (W×D×H)	440×301.5×70.1mm (17.3"×11.8"×2.7")	